



UNPOLISHED NATURAL STONE AND AGGLOMERATES



WHAT IT'S FOR

- Gives wet look to untreated surfaces (tumble finishes, flame finishes, natural sawn finishes).
- Protects material from water and oil.
- Consolidating effect treatment.

ADVANTAGES

- Provides a wet effect that can be intensified with several applications.
- Does not yellow with ageing or due to any environmental condition.
- Does not scrape from surface.

HOW TO USE IT

No dilution required: ready to use.

Application:

1. On a clean and dry surface, apply one even and continuous coat of FILAWET with a brush
2. After 24 hours repeat treatment in the same way.
3. For very absorbent materials, a third coat may be required to reach the desired wet effect.

Maintenance: diluted solutions of FILACLEANER. In the areas most exposed to weather conditions we recommend applying the product again every two years.

Caution:

Do not apply the product externally if rain is forecast during the following 24 hours. Do not walk on floor while it's drying: wait 24 hours after last product application. In the areas most exposed to weather conditions we recommend applying the product again every two years. Do not apply on terracotta floors or polished/very smooth surfaces. If product has been wrongly applied or if a thorough cleaning is required, remove FILAWET using FILANOPAINT STAR.

COVERAGE

With one litre:

10/20 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1-litre cans in boxes of 12.
5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- If used indoors, it is advisable to ventilate the area well.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES
Storage temperature: from 0° to 30°C
The product should be applied to materials with temperature between 5° and 30° C.

COMPOSITION
Synthetic resins dispersed in aromatic hydrocarbon solvent. Pursuant to It.Leg.Dec. No.161/06 class: Fixative primers (consolidator)
EU limit value for this product (Cat: 1/h): 750 g/l (2010)
This product contains no more than 739.20 g/l

LABELLING
Warning: Danger
Hazard indication: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.



Caution recommendations: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED:

Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations.
Contains: SOLVENT NAPHTA (PETROLEUM), LIGHT AROM.

TECHNICAL FEATURES

Appearance: viscous liquid
Colour: transparent
Odour: typical of aromatic solvent
Density: 0.908 kg/l
Flash point: 40 °C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.